

ANGLE	± 5°	REV	LOCAS	DESCRIPTION	DESIGN	DATE	卫国峰
X.XXX	± 0.05	01			DRAWN	DATE	尚伟
X.XX	± 0.15	02			CHECKED	DATE	吴汉学
X.X	± 0.25	03			AUDITED	DATE	龚劲松
X	± 0.50	04			APPROVED	DATE	eric

Specifications/备注 (Remark)

1-材料 (MATERIAL)

胶芯: PA6T/PBT+30%G.F UL94V-0, 颜色: 黑色

Housing:PA6T/PBT+30%G.F UL94V-0,Color:Black

四方针：黄铜/镍底30u"MIN/表面镀金0.8u"MIN

Contact: Brass/0.8u"MIN GOLD PLATING
OVER ALL 30u"MIN NICKEL UNDERPLATING
OVER ALL

2-特性 (characteristics):

额定电流: 3 AMP

Raring Current:3 AMP .

接觸阻抗: 20mΩ MAX.

Contact Resistance: 20mΩ MAX.

绝缘阻抗: 1000MΩMIN.

Insulating Resistance:1000MΩMIN.

耐电压: AC 500V.

Withstanding Voltage:AC 500V.


温度范围: -40度至+105度

Temperature Range: -40°C to +105°C

ORDERING INFORMATION

3690-2 XX XX X SX X 1

	NO.OF PINS PER ROW 06-64P	INSULATOR MATERIAL B:PA6T C:PA9T D:LCP	PACKING A:PE Bag B:TOPE&REED C:TUBE D:TUBE+CAP E:TRAY
HEIGHT OF HOUSING 90:9.0mm	CONTACT PLATING FULL OF GOLD SEMI-GOLD A0=0.8u" B0=0.8U" A9=30u" B9=30U" S1=ORDINARY TIN PLATED S2=MATTE TIN PLATED S3=TIN-PLATED HIGH-TEMPERATURE		



YLIES® 东莞市瑞翔精密连接器有限公司
DONG GUAN YLIES PRECISE CONNECTOR CO.,LTD

Tel:0769-85381995 / Fax:0769-85493987 / Email: ylies@ylies.cn / Web:www.ylies.cn

PROJECTON		REV A	UNIT mm	SCALE 1:1	PAGE 1/1
-----------	---	----------	------------	--------------	-------------

TITLE

198-2.54mm 简易牛角 180度加塑胶

DATE _____

2018-02-18

PART NO:

3690-2XXXXXSXX1

DRAWING NO: